



QFCU (QFCI MUD)

Loose tube, jelly filled

Armoured

SHF2 MUD, UV

DNV

Application

Fiberoptical cable for use in vital communication and emergency systems, which needs to be operational during a fire situation (90 min. 1000°C). The fibers are protected in jelly filled loose tubes stranded around a central strength member to ensure high performance and long endurance. Individual colours for each fiber. 62.5, 50 and 9 µm fibers. MUD resistant jacket.



Construction Fiber

Fibertype	MM 62.5 and 50, SM 9
Sub unit sheath	PBTP with jelly
Colorcode fiber	TIA 598 1 - Blue 5 - Grey 9 - Yellow 2 - Orange 6 - White 10 - Violet 3 - Green 7 - Red 11 - Pink 4 - Brow 8 - Black 12 - Turquoise
Fiber tube	Loose tube Ø = 2.2 [mm], Mica tape on each loose tube
Fire resistant barrier	Mica tape
Strength member	Centre steel wire
Inner jacket	Black SHF1
Armour	Alt. 1 - Galvanised steel wire braid Alt. 2 - Tinned Cu-braid Alt. 3 - Bronze wire braid
Jacket	Black SHF2 MUD-resistant
Diameter	16.5 [mm]
Weight	350 [kg/km]

Specifications

Operating temperature normal	-40 – +70 [°C]
Temperature @ installation	-10 to +60 [°C]
Tensile strength	500 acc. to IEC 60794-1-2
Crush test	3000 [N/10cm] acc. to IEC 60794-1-2 (E3)
Impact	30 [J] acc. to IEC 60794-1-2 (E4)
Torsion	±1 [turn/m]
Min. bending radius	15 [x outer diam]
Min. bending radius flexible	20 [x outer diam]



Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1 & IEC 60754-2
Material properties, insulation and sheath	IEC 60092-360 (359)
Fire resistant	IEC 60331-25 min. 1000°C
Ozone resistant	IEC 60811-2-1
Smoke emission	IEC 61034-1 & IEC 61034-2
Oil and fuel resistant	IEC 60811-2-1 EN 60811-404 IRM 903
MUD resistant	NEK TS 606 F5
UV-resistant	ISO 4892-2-A: 720hours
Certification	DNV



Table Fiber

Number of fibers	Number of fibers per tube	Number of fibers and tubes	Weight [kg/km]	Part no.
4 - 62,5/125	2	2 + 4	325	1091114
8 - 62,5/125	4	2 + 4	325	1091115
12 - 62,5/125	4	3 + 3	325	1091116
24 - 62,5/125	6	4 + 2	325	1091117
48 - 62,5/125	12	4 + 2	325	1091126
4 - 50/125 OM3	2	2 + 4	325	1091125
8 - 50/125 OM3	4	2 + 4	325	1091118
12 - 50/125 OM3	4	3 + 3	325	1091119
24 - 50/125 OM3	6	4 + 2	325	1091124
48 - 50/125 OM3	12	4 + 2	325	1091146
4 - 50/125 OM2	2	2 + 4	325	1042464
8 - 50/125 OM2	4	2 + 4	325	1042465
12 - 50/125 OM2	4	3 + 3	325	1042466
24 - 50/125	6	4 + 2	325	1042467
48 - 50/125	12	4 + 2	325	1091150
4 - 9/125	2	2 + 4	325	1091147
8 - 9/125	4	2 + 4	325	1091191
12 - 9/125	4	3 + 3	325	1091192
24 - 9/125	6	4 + 2	325	1091193
48 - 9/125	12	4 + 2	325	1091194



Fiber data

Properties	MM 62.5 OM1	MM 50 OM2	MM 50 OM3	MM 50 OM4
Core Diameter	62.5 ± 2.5 µm	50 ± 2.5 µm	50 ± 2.5 µm	50 ± 2.5 µm
Core non-circularity	< 5%	< 5%	< 5%	< 5%
Cladding diameter	125 ± 1.0 µm	125 ± 1.0 µm	125 ± 1.0 µm	125 ± 1.0 µm
Coating diameter	242 ± 5 µm	242 ± 5 µm	242 ± 5 µm	242 ± 5 µm
Cladding non-circularity	<0.7%	<0.7%	<0.7%	<0.7%
Core/Cladding concentricity error	<1 µm	<1 µm	<1 µm	<1 µm
Coating/cladding concentricity error	<10 µm	<6 µm	<6 µm	<6 µm
Numerical Aperture	0.275 ± 0.015 µm	0.200 ± 0.015 µm	0.200 ± 0.015 µm	0.200 ± 0.015 µm
Attenuation @ 850 nm	<3.50 dB/km	<2.89 dB/km	<2.89 dB/km	<2.89 dB/km
Attenuation @1300 nm	<1.00 dB/km	<0.80 dB/km	<0.80 dB/km	<0.80 dB/km
Bandwidth @ 850 nm	>200 MHz*km	>500 MHz*km	>1500 MHz*km	>3500 MHz*km
Bandwidth @ 1300 nm	>500 MHz*km	>500 MHz*km	>500 MHz*km	>500 MHz*km
Effective Modal Bandwidth (EMB)@ 850 nm			>2000 MHz*km	>4700 MHz*km
Fibre capacity 10GBase-SR	33 m	83 m	300 m	550 m
Fibre capacity 1GBase-SR	274 m	600 m	1000 m	1100 m
Fibre cap. 40GBase-SR4/100Base-RS10	274 m	600 m	1000 m	1100 m
Fibre cap. 40GBase-SR4/100Base-RS10			140 m	1740 m
Proof test	>100kpsi	>100kpsi	>100kpsi	>100kpsi



Properties	SMR ITU-T G652D	SMR ITU-T G657A	SMR ITU-T G657B / - B2	SMR NZD ITU-T G655.E
Mode field Diameter @ 1310 nm	9,0±0,4 μm	9,0±0,4 μm	8,9±0,5 μm	-
Mode field Diameter @ 1550 nm	10,1±0,5μm	10,1±0,5μm	9,9 ± 0,5 μm	9,2 ± 0,5 μm
Cladding diameter	125±0,7 μm	125±0,7 μm	125±0,7 μm	125±01,0 μm
Coating diameter	242±7 μm	242±7 μm	242±7 μm	242±7 μm
Cladding non-circularity	≤ 0,7 %	≤ 0,7 %	≤ 0,7 %	≤ 1,0 %
Core/Cladding concentricity error	≤ 0,5 μm	≤ 0,5 μm	≤ 0,5 μm	≤ 0,6 μm
Coating/cladding concentricity error	≤ 12 μm	≤ 12 μm	≤ 12 μm	≤ 12 μm
Cable Cut off wavelength	≤ 1260 nm	≤ 1260 nm	≤ 1260 nm	≤ 1300 nm
Zero dispersion wavelength (λ ₀)	1300-1322 μm	1300-1322 μm	1300-1322 μm	1440 μm
Dispersion slope (S ₀) @ (λ ₀)	≤ 0,090 ps/(nm ² * km)	≤ 0,090 ps/(nm ² * km)	≤ 0,092 ps/(nm ² * km)	-
Chromatic dispersion @ 1285-1330 nm	≤ 3,5 ps/(nm * km)	≤ 3,5 ps/(nm * km)	-	-
Chromatic dispersion @ 1550 nm	≤ 18 ps/(nm * km)	≤ 18 ps/(nm * km)	-	-
Chromatic dispersion @ 1625 nm	≤ 22 ps/(nm * km)	≤ 22 ps/(nm * km)	-	-
Chromatic dispersion @ 1530-1565 nm	-	-	-	5,5 - 10 ps/(nm * km)
Chromatic dispersion @ 1565-1625 nm	-	-	-	7,5 - 13,8 ps/(nm * km)
PMD @ 1550 nm	≤ 0,1 ps/√ km	≤ 0,1 ps/√ km	≤ 0,1 ps/√ km	≤ 0,2 ps/√ km
Attenuation @ 1310 nm	≤ 0,35 dB/km	≤ 0,35 dB/km	≤ 0,35 dB/km	≤ 0,40 dB/km
Attenuation @ 1383nm	≤ 0,35 dB/km	≤ 0,35 dB/km	≤ 0,35 dB/km	≤ 1,0 dB/km
Attenuation @ 1550 nm	≤ 0,25 dB/km	≤ 0,25 dB/km	≤ 0,25 dB/km	≤ 0,25 dB/km
Attenuation with bending:				
Mandreal Radius 15mm @1550 10 turns	-	≤ 0,25 dB	≤ 0,03 dB	-
Mandreal Radius 15mm @1625 10 turns	-	≤ 1,0 dB	≤ 0,1 dB	-
Mandreal Radius 10mm @1550 1 turn	-	≤ 0,75 dB	≤ 0,1 dB	-
Mandreal Radius 10mm @1625 1 turn	-	≤ 1,5 dB	≤ 0,2 dB	-
Mandreal Radius 7,5mm @1550 1 turn	-	-	≤ 0,5 dB	-
Mandreal Radius 7,5mm @1625 1 turn	-	-	≤ 1,0 dB	-
Proof test	≥ 100 kpsi	≥ 100 kpsi	≥ 100 kpsi	≥ 100 kpsi



Updated

Date	Rev.	Description
16.03.2015	1	Armour
28.12.2015	2	Revision of part. no.
23.01.2017	3	Fiber data
06.06.2019	4	Colour code
4.12.2019	5	Updated construction (double jacket)
01.03.2023	6	Colour code to TIA 598
13.12.2024	7	Additional info