



AIAI - UNI

Tight buffered fiber optic cable with strong glass yarn shield

Non metallic, waterproof

Up to 12 fibers

SHF1, UV

DNV

Application

This product is absolutely immune against electromagnetic or electrical disturbances in its environment. It is also mechanically strong and waterproof. It is ideal for communication and data transmission in harsh environments as shipboard- and offshore installations close to electrical machinery and power lines. The cable can also be delivered with SHF2 MUD-resistant outer jacket, AIAU.



Construction Fiber

| | |
|------------------|---|
| Fibertype | Tight buffer 0,9 mm |
| Colorcode fiber | 1 - Blue 7 - Red 2 - Orange 8 - Black 3 - Green 9 - Yellow 4 - Brown 10 - Violet 5 - Grey 11 - Pink 6 - White 12 - Turquoise |
| Moisture barrier | Glass yarn |
| Inner jacket | SHF1 |
| Armour | Aramid yarn |
| Jacket | Black SHF1, UV-resistant. Also available with SHF2 MUD, other colours on request |
| Diameter | See table |
| Weight | See table |

Specifications fiber

| | |
|--------------------------|--|
| Fiber type | Tight buffer 0,9 mm |
| Temperature range | -40 – 70 [°C] SHF1 -40 – 90 [°C] SHF2 MUD |
| Tensile strength | 2000 [N] Δα reversible (IEC 60794-1-2-E1) |
| Crush resistance | 2000 [N/100mm] (IEC 60794-1-2-E3) |
| Impact resistance | 20 [J] Δα reversible (IEC 60794-1-2-E4) |
| Water penetration | No water penetration (IEC 60794-1-2-F5) |
| Bending radius flexible | 15 [x outer diam.] |
| Bending radius installed | 10 [x outer diam.] |



Norms

| | |
|--|---------------------------|
| Halogenfree, max content corrosive and toxic gases | IEC 60754-1 & IEC 60754-2 |
| Material properties, insulation and sheath | IEC 60092-360 (359) |
| Flame resistance | IEC 60332-3-22 |
| Flame retardant | IEC 60332-1 |
| Smoke emission | IEC 61034-1 & IEC 61034-2 |
| UV-resistant | ISO 4892-2-A: 720hours |
| Certification | DNV |



ABS certificated can be prodced if required.

Fiber data

| Properties | MM 62.5 OM1 | MM 50 OM2 | MM 50 OM3 | MM 50 OM4 |
|---|------------------|------------------|------------------|------------------|
| Core Diameter | 62.5 ± 2.5 µm | 50 ± 2.5 µm | 50 ± 2.5 µm | 50 ± 2.5 µm |
| Core non-circularity | < 5% | < 5% | < 5% | < 5% |
| Cladding diameter | 125 ± 1.0 µm | 125 ± 1.0 µm | 125 ± 1.0 µm | 125 ± 1.0 µm |
| Coating diameter | 242 ± 5 µm | 242 ± 5 µm | 242 ± 5 µm | 242 ± 5 µm |
| Cladding non-circularity | <0.7% | <0.7% | <0.7% | <0.7% |
| Core/Cladding concentricity error | <1 µm | <1 µm | <1 µm | <1 µm |
| Coating/cladding concentricity error | <10 µm | <6 µm | <6 µm | <6 µm |
| Numerical Aperture | 0.275 ± 0.015 µm | 0.200 ± 0.015 µm | 0.200 ± 0.015 µm | 0.200 ± 0.015 µm |
| Attenuation @ 850 nm | <3.50 dB/km | <2.89 dB/km | <2.89 dB/km | <2.89 dB/km |
| Attenuation @1300 nm | <1.00 dB/km | <0.80 dB/km | <0.80 dB/km | <0.80 dB/km |
| Bandwidth @ 850 nm | >200 MHz*km | >500 MHz*km | >1500 MHz*km | >3500 MHz*km |
| Bandwidth @ 1300 nm | >500 MHz*km | >500 MHz*km | >500 MHz*km | >500 MHz*km |
| Effective Modal Bandwidth (EMB)@ 850 nm | - | - | >2000 MHz*km | >4700 MHz*km |
| Fibre capacity 10GBase-SR | 33 m | 83 m | 300 m | 550 m |
| Fibre capacity 10GBase-LX4 | 274 m | 600 m | 1000 m | 1100 m |
| Fibre cap. 40GBase-SR4/100Base-RS10 | - | - | 140 m | 170 m |
| Proof test | >100kpsi | >100kpsi | >100kpsi | >100kpsi |



| Properties | SMR ITU-T G652D | SMR ITU-T G657A | SMR ITU-T G657B / - B2 | SMR NZD ITU-T G655.E |
|--|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------|
| Mode field Diameter @ 1310 nm | 9,0±0,4 µm | 9,0±0,4 µm | 9,0±0,4 µm | - |
| Mode field Diameter @ 1550 nm | 10,1±0,5µm | 10,1±0,5µm | 9,9±0,5µm | 9,2±0,5µm |
| Cladding diameter | 125±0,7µm | 125±0,7µm | 125±0,7µm | 125±1,0µm |
| Coating diameter | 242±7 µm | 242±7 µm | 242±7 µm | 242±7 µm |
| Cladding non-circularity | ≤ 0,7 % | ≤ 0,7 % | ≤ 0,7 % | ≤ 0,7 % |
| Core/Cladding concentricity error | ≤ 0,5 µm | ≤ 0,5 µm | ≤ 0,5 µm | ≤ 0,5 µm |
| Coating/cladding concentricity error | ≤ 12 µm | ≤ 12 µm | ≤ 12 µm | ≤ 12 µm |
| Cable Cut off wavelength | ≤ 1260 nm | ≤ 1260 nm | ≤ 1260 nm | ≤ 1300 nm |
| Zero dispersion wavelength (λ_0) | 1300-1322 µm | 1300-1322 µm | 1300-1324 µm | 1440 µm |
| Dispersion slope (S_0) @ (λ_0) | ≤ 0,090 ps/(nm ² * km) | ≤ 0,090 ps/(nm ² * km) | ≤ 0,092 ps/(nm ² * km) | - |
| Chromatic dispersion @ 1285-1330 nm | ≤ 3,5 ps/(nm * km) | ≤ 3,5 ps/(nm * km) | - | - |
| Chromatic dispersion @ 1550 nm | ≤ 18 ps/(nm * km) | ≤ 18 ps/(nm * km) | - | - |
| Chromatic dispersion @ 1625 nm | ≤ 22 ps/(nm * km) | ≤ 22 ps/(nm * km) | - | - |
| Chromatic dispersion @ 1530-1565 nm | - | - | - | 5,5 - 10 ps/(nm * km) |
| Chromatic dispersion @ 1565-1625 nm | - | - | - | 5,5 - 10 ps/(nm * km) |
| PMD @ 1550 nm | ≤ 0,1 ps/√ km | ≤ 0,1 ps/√ km | ≤ 0,1 ps/√ km | ≤ 0,2 ps/√ km |
| Attenuation @ 1310 nm | ≤ 0,35 dB/km | ≤ 0,35 dB/km | ≤ 0,35 dB/km | ≤ 0,40 dB/km |
| Attenuation @ 1383nm | ≤ 0,35 dB/km | ≤ 0,35 dB/km | ≤ 0,35 dB/km | ≤ 0,40 dB/km |
| Attenuation @ 1550 nm | ≤ 0,25 dB/km | ≤ 0,25 dB/km | ≤ 0,25 dB/km | ≤ 0,25 dB/km |
| Attenuation @ 1625 nm | ≤ 0,28 dB/km | ≤ 0,28 dB/km | ≤ 0,28 dB/km | ≤ 0,28 dB/km |
| Attenuation with bending: | | | | |
| Mandreal Radius 15mm @1550 10 turns | - | ≤ 0,25 dB | ≤ 0,03 dB | - |
| Mandreal Radius 15mm @1625 10 turns | - | ≤ 1,0 dB | ≤ 1,0 dB | - |
| Mandreal Radius 10mm @1550 1 turn | - | ≤ 0,75 dB | ≤ 0,1 dB | - |
| Mandreal Radius 10mm @1625 1 turn | - | ≤ 1,5 dB | ≤ 0,2 dB | - |
| Mandreal Radius 7,5mm @1550 1 turn | - | - | ≤ 0,5 dB | - |
| Mandreal Radius 7,5mm @1625 1 turn | - | - | ≤ 1,0 dB | - |
| Proof test | ≥ 100 kpsi | ≥ 100 kpsi | ≥ 100 kpsi | ≥ 100 kpsi |



| No. of fibre | Diam. inner sheath [mm] | Diam. outer sheath [mm] | Weight [kg/km] |
|--------------|-------------------------|-------------------------|----------------|
| 4 | 5,2 | 8,5 | 90 |
| 8 | 6,0 | 9,4 | 100 |
| 12 | 6,7 | 10,3 | 115 |

Updated

| Date | Rev. | Description |
|------------|------|-----------------|
| 10.04.2019 | 1 | Properties |
| 13.12.2024 | 2 | Additional info |